LMS Event Data Field	Acceptable CSV Values for the Field	Notes about Field
Session ID	Numeric	This field is the internal session identifier in a specific platform database; it is determined by the platform and cannot be edited or removed.  One between Session ID and the Session UUID are mandatory, but both fields cannot have values in the same CSV row or you will receive an importing error.
Session UUID	String	Unique alphanumeric session identifier, automatically calculated by the platform when the course is created. It cannot be edited or removed.  One between Session ID and the Session UUID are mandatory, but both fields cannot have values in the same CSV row or you will receive an importing error.  This is field is case sensitive
Event ID	Numeric	Unique event identifier, automatically calculated by the platform when the course is created. It cannot be edited or removed.  When this field is set, the import process will update the event with the CSV data.
Event Name	String	
Event Description	String	
Event Date	YYYY-MM-DD (Example: 2021-04-29)	
Event Start Time	HH:mm:ss (Example: 09:00:00)	This field is mandatory
Event End Time	HH:mm:ss (Example: 18:00:00)	This field is mandatory

Break Start Time	HH:mm:ss (Example: 13:00:00)	The break time is optional, but when used both <i>Break Start Time</i> and <i>Break End Time</i> must be specified.  The <i>Break Start Time</i> must occur after the <i>Event Start Time</i> .
Break End Time	HH:mm:ss (Example: 14:00:00)	The break time is optional, but when used both <i>Break Start Time</i> and <i>Break End Time</i> must be specified.  The <i>Break End Time</i> must occur before the <i>Event End Time</i> .
Time Zone	Region/Local (Example: "Europe/Rome")	Must match the timezone name format (without GMT + XX:XX) in the platform. Find the full list in the <i>Advanced Settings</i> area, <i>Date and Time</i> tab. For example, the time zone format for Jerusalem is "Asia/Jerusalem", while for Prague is "Europe/Prague".  This field is case-sensitive.
Instructor User ID(s)	Numeric (array) (Example: 1105,2347,7231)	List of the event's instructors, identified by their User ID.  *Instructor User ID(s)* and *Instructor Username(s)* are optional, but both fields cannot coexist in the same CSV row or or the import procedure will return an error.
Instructor Username (s)	String or numeric (array)	List of the event's instructors, identified by their <i>Username</i> .  Instructor User ID(s) and Instructor Username(s) are optional, but both fields cannot coexist in the same CSV row or the import procedure will return an error.  This is field is case sensitive.
Location ID	Numeric	Location identifier. It is determined by the platform and cannot be edited or removed.  Every event must have a <i>Location ID</i> or a <i>Webinar Tool</i> , or both.

Classroom ID	Numeric	Classroom identifier. It is determined by the platform and cannot be edited or removed.  This is an optional field, that can be specified when Location ID is set.
Collaboration Tool	String	Optional text to specify an external collaborative tool for learners to get in touch and interact on the course topic.
Video Conference Tool	String	Use this field to set the Video Conference Tool for the vILT event.  Accepted values are:     - zoomv2webinar     - zoomv2meeting     - webexv2meeting     - webexv2event     - webexv2training     - adobeconnectv2meeting     - adobeconnectv2seminar     - gotomeetingv2meeting     - gotomeetingv2training     - gotomeetingv2vebinar     - msteamsv2event     - msteamsv2event     - msteamsv2meeting     - custom  This is field is case sensitive.
Video Conference Account ID	Numeric	Internal webinar account identifier. It is determined by the platform and cannot be edited or removed.  It becomes a mandatory field when the <i>Webinar Tool</i> option is enabled and it is not set to "custom".  It must not be used in other cases.

Passcode / Meeting Password	String	Password to access the webinar. It becomes a mandatory field when the Webinar Tool option is enabled and it is not set to "custom". If not specified, the system will automatically generate a password for the webinar.
Video Conference Custom URL	String	This field is mandatory when the Webinar Tool is set to "custom". It must not be used in other cases.
Mark the event as attended if the user accesses the recordings	false / true	This field is mandatory when a Webinar Tool is specified.
Mark the event as attended when the user joins the webinar	false / true	This field is mandatory when a Webinar Tool is specified.
Join In Advance Time For Learner	HH:mm (Example: 00:05)	This field is optional and can be used only when a <i>Webinar Tool</i> is specified and when configuring the <i>Join Button Options</i> for learners and instructors.  The learner <i>join in advance</i> time cannot be earlier than the <i>Instructor</i> one.
Join In Advance Time For Instructor	HH:mm (Example: 00:15)	This field is optional and can be used only when a Webinar Tool is specified and when configuring the Join Button Options for learners and instructors.  The learner join in advance time cannot be earlier than the Instructor one.
Adobe Connect % for Completion	Numeric	This field is optional and can be used only when a Webinar Tool is set to Adobe Connect V2 Meeting or Webinar
Adobe Connect v2 Template	String	This field is optional and can be passed as an empty string. It represents the SCO-ID of the template in the AdobeConnect V2 Account.
Adobe Connect v2 Folder	String	This field is optional and can be passed as an empty string. It represents the SCO-ID of the folder in the AdobeConnect V2 Account.

Adobe Connect v2 Room	String	This field is optional and can be passed as an empty string. It is mandatory when using <i>Adobe Connect V2 Seminar</i> as video conference tool. It represents the SCO-ID of the room in the AdobeConnect V2 Account.
--------------------------	--------	--